

S80 COUNTERTOP PAYMENT TERMINAL

🔒 PCI PTS 3.x certified

🔒 Ethernet, Modem

🔒 Contactless / NFC



PAX's S80 is an advanced countertop POS terminal which combines innovation, durability and high performance to assure faster, more reliable transactions.

The PCI PTS 3.x approved S80 offers advanced connectivity, equipped with various communication technologies such as Ethernet and PSTN. An intuitive ATM-style interface and ergonomic keypad make operation easier for merchant and consumer alike.

The S80 comes with built-in contactless and powerful ARM11 processor, enabling support for multiple payment and value-added applications, making this countertop terminal one of the most reliable in the world.

S80 COUNTERTOP PAYMENT TERMINAL

SPECIFICATIONS

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB SDRAM)

Display

128 x 64 pixel LCD, White backlit

Keypad

10 numeric / letter & 8 function keys
4 ATM keys, 1 Power ON / OFF key

Printer

Thermal printer, Speed: 25 lps
Standard paper roll: 58mm (2.25 in.)

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional, ISO7812

Smart Card Reader

1 user card, EMV

Contactless Card Reader (built-in)

13.56MHz, ISO14443 Type A/B, Mifare,

Felica, NFC

Maximum effective distance up to 4cm
4 RF Indicators: Blue, Yellow, Green, Red

Card Slots

3 SAMs, ISO7816

Communication

Modem:
Sync. (HDLC up to 9600bps);
Asnyc. (V.92, up to 56kbps)
Ethernet (optional)

Peripheral Ports

1 x PINPad, 1 x RS232, 1 x Ethernet,
1 x Line, 1 x mini USB (OTG)

Security

PCI PTS 3.x approved
DUKPT, Master / Session, DES, 3DES
ANSI / ISO9564 format 0,1,3
PIN ciphered key algorithm
ANSI X9.9 / X9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 122°F) operating
temperature

-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing

Voltage

Input: 100~240VAC, 50Hz / 60Hz, 1.5A
Output: 8.2VDC, 3A

Physical

Length: 216mm (8.5 in.)
Width: 95mm (3.74 in.)
Height: 86 mm (3.390 in.)

Weight

525g

Certifications

PCI PTS 3.x
EMV (Level1 & Level2)

FEATURES

- High speed ARM 11 processor
- Large Memory Capacity
- USB
- Optional built-in Contactless



Corporate Headquarters

4/F, No.3 Building, Software Park,
2nd Central Science-Tech Road,
High-Tech Industrial Park,
Shenzhen 518057,
P.R. C.
T: +86 755 8616 9630
F: +86 755 8616 9634
E: market@paxsz.com

North America

4901 Belfort Road
Suite 130,
Jacksonville,
FL 32256,
USA
T: +1 904 900 3741
E: inquiry@pax.us

Asia Pacific

Room 2416, 24/F.,
Sun Hung Kai Centre,
30 Harbour Road,
Wanchai,
Hong Kong
T: +852 2500 8500
F: +852 2598 0299

EMEA Region

Portland House
16th Floor
Bressenden Place
London SW1E 5RS
United Kingdom
T: +44 (0)208 433 6570
F: +44 (0)207 869 8001
E: EMEA@paxsz.com

LACIS Region

4/F, No.3 Building, Software Park,
2nd Central Science-Tech Road,
High-Tech Industrial Park,
Shenzhen 518057,
P.R. C.
T: +86 755 8616 9630
F: +86 755 8616 9634
E: LACIS@paxsz.com

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

PAX are either trademarks or registered trademarks of PAX Technology in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. Copyright 2012, PAX Technology. All Rights Reserved.