A35

Integrated Smart PINpad

The A35 is a next-generation Smart PIN pad with PAXBiz® powered by Android™ 10. This high-performance payment terminal is designed to support in-device semi-integration payment applications, or it can be used as a payment input peripheral interfacing to another device that manages the payment application.

Easily integrated with any POS system, it is the perfect solution for personalizing the payment experience and offering value-added services at the point of sale, such as loyalty programs, advertising, and data entry (surveys).

The A35 adheres to the latest PCI PTS 6.x and SRED payment industry security standards, features a vivid touchscreen display, and has an innovative cable design that provides high-speed Ethernet, as well as Power-Over-Ethernet or USB power. In addition to accepting standard card-based payment, the A35 is equipped to accept touchless payments such as contactless (NFC) and QR codes.

SUPERMARKETS | FOOD & BEVERAGE | FASHION & RETAIL

PayFacto

Expertise · Agility · Execution

A35

Integrated Smart PINpad

MAIN FEATURES

- Features our latest operating system, PAXBiz® powered by Android™

- Adheres to the latest PCI PTS 6.x and SRED security standards

- Accepts contactless, EMV, and magnetic stripe payments

- Features a vivid, four-inch capacitive touchscreen

- Innovative cable design that incorporates high-speed Ethernet, RS232, and USB, as well as optional Power-Over-Ethernet

SPECIFICATIONS

Operating System	PayDroid Powered by Android 10.x
Processor	Quad-core Cortex A53, 1.6GHz
Memory	8GB Flash + 1GB DDR, 128GB MicroSD Optional
Card Readers	Chip & PIN	NFC Contactless	Magnetic Stripe
Cameras	0.3MP Fixed Front-Facing, 5MP Fixed Front-Facing Optional
Displays	4'' WVGA 480 x 800 Pixels, Capacitive Touch Screen
Comms Configurations	RS232	Ethernet (Gigabit Optional)	USB 2.0	Wi-Fi® (2.4GHz/5GHz) + Bluetooth® (4.2/5.0) (Optional)
Adapter	Input: 100-240VAC, 50Hz/60Hz	Output: 5.0V DC, 1.0A
SIM / SAM	2 PSAM
Keys / Buttons	13 keys: 0-9	Enter	Clear	Cancel, Back-Lighting (Optional)
Audio	1 Speaker	1 Audio Jack
Ports	Multi-Functional Port	1 Kensington	MicroSD (Optional)
Physical	163.69mm x 76.90mm x 30.10mm(L x W x H)	260g
Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 93% Relative Humidity, Non-Condensing
Accessories	Multiple Cabling Options	Stand
Certifications	PCI PTS 6.x, SRED	EMV L1 & L2	EMV Contactless L1	Visa payWave	MasterCard Contactless	UPI qUICS	Amex ExpressPay	Discover D-PAS	JCB J/Speedy	Interac Flash	MasterCard TQM	UL	FCC	IC	CE	RoHs

PayFacto

Expertise · Agility · Execution

US: 1-800-465-2400
info@payfacto.com

payfacto.com